## Cessna 680 Sovereign **Certified Sealed Lead Acid Battery Installation FAA STC ST04366AT TCCA STC SA19-4 EASA STC 10068718** Main Battery Upgrade -Marathon 9914058-6 (24V, 44Ah) is replaced with either

RG-380E/60L (24V, 48Ah) or RG-380E/53L (24V, 53Ah).

• Lower cost of acquisition

- Increased capacity
- Reduced cost per flight hour
- No deep cycling requirement
- No part replacements
- Hazmat Exempt
- 100% recyclable the green solution

Made in the U.S.A.

STC provides for the installation of two Concorde RG-380E/53L or RG-380E/60L, fitted with temperature sensors TS-C1B, in place of the original equipment nickel cadmium batteries.

- 1) Install TS-C1B on each Concorde battery.
- 2) Aircraft fitted with Cessna Washer P/N 5538330-35 may require slight modification to washer in order to allow for proper fitment with the Concorde battery hold-down bar as detailed in the STC.
- 3) Batteries are drop-in replacements installed in accordance with the Cessna 680 Aircraft Maintenance Manual.

STC includes two TS-C1B temperature sensor kits (P/N 5-0121).


## **CONCORDE BATTERY CORPORATION**

2009 San Bernardino Road | West Covina, CA 91790 USA 626-813-1234 | Fax 626-813-1235 | www.ConcordeBattery.com ISO 9001 + AS9100 | Crafted for Quality in the U.S.A.



RG-380E/53L, 53Ah Higher Capacity

or RG-380E/60L, 48Ah



Part	Rated Capacity	IPP	IPR	IPP	IPR	IPP	IPR	Maximum
Number	C1 in Ah	23°C / 74°F		-18°C / 0°F		-30°C / -22°F		Weight
RG-380E/53L	53Ah	1650	1200	1325	1000	1125	800	96 LB/43.6 KG
RG-380E/60L	48Ah	1600	1200	1200	950	900	700	96 LB/43.6 KG

## Miscellaneous

**P/N 5-0121 Kit** – Includes 2 @ TS-C1B Temperature Sensor kits

Installation instructions included

## **CONCORDE BATTERY CORPORATION**

2009 San Bernardino Road | West Covina, CA 91790 USA 626-813-1234 | Fax 626-813-1235 | www.ConcordeBattery.com ISO 9001 + AS9100 | Crafted for Quality in the U.S.A.

